

Touch & Numeric UIDNIE DUO GCD coffee machines



WINNING DUO GCD

coffee machines

- High-impact design in line with the Snack&Food models
- LED lighting of the photographic panels
- Two types of coffee in beans
- Five soluble products for 4 mixers
- Traditional FAS EBG espresso unit
- 2 FAS professional MF1 grinder/metering units with flat blades
- Automatic recognition of own cup (optional)
- Self-extracting mixers
- 650 cc heater with mixing solenoid valve for differentiating the temperatures of the solubles
- Rielda RS1 Lock
- Energy saving function
- Programming, cloning, and Audit functions using a standard USB pen drive
- 32 bit electronics with USB 2.0 HOST

Touch Interface Version

- 19" surface wave touch screen
- Interactive customizable user menu (images, recipes, film footage, etc.)
- Graphically guided touch personalization and programming

Numerical Interface Version

- Metal numerical selection keypad with vandal-proof features
- Central backlit user menu with up to 89 recipes for maximum flexibility
- Management of the options without sugar, with sugar, extra sugar, without preselection
- Centrally positioned graphic display for maximum user visibility
- Graphic colour display 480 x 272 pixel with the possibility of personalised slide shows and / or visualization of supplementary information (ex: product ingredients and nutritional value)
- Illuminated keyboard



Winning Duo GCD Touch + Faster GCD 900



Mixing solenoid valve to guarantee differentiated and optimal temperatures in the solubles




Two flat-blade MF1 professional grinders



Two types of coffee with independent grinding and dosage



High-performance touch screen



E_8

1 = Sugar (on door) 2 = Tea 3 = Chocolate

2,7 kg 4,0 kg 4 = Milk

5 = Instant coffee 1 6 = Instant coffee 2

7 = Coffee beans 1 8 = Coffee beans 2 2,0 kg

1,0 kg





Winning Duo GCD _ black

Winning Duo GCD Touch _ silver

General Features		Winning Duo	Winning Duo Touch
Height	mm	1830	1830
Width	mm	760	760
Depth	mm	700	700
Depth with open door	mm	1560	1560
Weight	Kg	175	185
Power supply	V / Hz	230 / 50	230 / 50
Power capacity	W	1600	1600
EVA-EMP consumption (idle mode)*	Wh/h	109	109
Water connection	Мра	0,1 / 0,8	0,1 / 0,8
Cups (166 cc)	n°	780	780
Stirrers	n°	585	585
Canisters	n°	8	8
Boiler	CC	pressure boiler 650	pressure boiler 650
Protocol		MDB Executive BDV	MDB Executive BDV
Direct selection	n°	Numerical	Touch
Graphical display		LCD 240x128 pixel	Touch Screen 19"
Standard version		black RAL 9005 & aluminium	silver & aluminium
Variant		silver & aluminium	black RAL 9005 & aluminium

 $^{{}^*\}textit{An EVA-EMP list indicating the power consumption of the machine is available on request.}$

